

# RTI CONTROL PROCESSOR COMPARISON CHART

	CONTROL PORTS						PROCESSING FEATURES			COMMUNICATION					POWER & MOUNTING			MEMORY			
	RS-232 2-Way	MPIO (Multi-Purpose I/O)	IR (Routeable)	Relay	12 VDC Trigger	Sense Input	2-Way Driver Support	Astronomical Clock	CPU Clock Rate	Ethernet	WiFi	RF 433 MHz	Zigbee 2.4 GHz	Expansion Port (connects RTI devices)	HDMI Output (OSD Support)	Power Supply	PoE	Rack-Mount	RAM	Internal Nonvolatile Flash Memory	SD Card Slot
ProLink.z <sup>9</sup>	2		6	2		2 <sup>2</sup>	●		532MHz	●			●			●			64MB	128MB	
RP-4			4	2		2 <sup>2</sup>			100MHz	●		●				●			128K	512K	
KX-3 <sup>8</sup>	2			4		6 <sup>3</sup>	●	●	532MHz	●	●		●			● <sup>6</sup>	●		256MB	128MB	
XP-3	1	1	2	2		2 <sup>2</sup>	●	●	532MHz	●			●			●	●		64MB	128MB	
VXP-82 <sup>10</sup>	2	6	6	3	3	3 <sup>2</sup>	●	●	532MHz	●		● <sup>4</sup>	● <sup>5</sup>	●		● <sup>7</sup>		●	64MB	128MB	
XP-6s	3	6	6	3	3	3 <sup>2</sup>	●	●	1GHz	●		● <sup>4</sup>	● <sup>5</sup>	●		● <sup>7</sup>		●	512MB	512MB	
XP-8v	8	8	8	8 <sup>1</sup>	8 <sup>1</sup>	8 <sup>3</sup>	●	●	1GHz	●		● <sup>4</sup>	● <sup>5</sup>	●	●	● <sup>7</sup>		●	1GB	512MB	●

<sup>1</sup> Relay or 12VDC Trigger Output

<sup>2</sup> Voltage

<sup>3</sup> Voltage or Contact Closure

<sup>4</sup> Via RM-433 (not included)

<sup>5</sup> Via ZM-24 (not included)

<sup>6</sup> Power Supply not included

<sup>7</sup> Rack Ears included

<sup>8</sup> 3.5" Inwall Touch Panel with built-in Control Processor

<sup>9</sup> Pro Control Processor. Compatible with all RTI remotes and KX1, KX2, KX3, KX7, KX10, KA8 & KA11 Touchpanels

<sup>10</sup> Control Processor with built-in <sup>8</sup>x<sup>2</sup> Presentation Switcher

