Unilumin



USlim-O 3 OUTDOOR SOLUTION

- Flexible Application.
- Flexible Dimensions, Available in: 500x500mm OR 500x1000mm.
- Easy Maintenance.
- Multiple Installation Methods.

Get Creative with Flexibility

USlim can curve +- % degrees thanks to its built-in curve adjustment. This flexibility make display application almost endless: Uslim is an excellent option for retail spaces, corporate lobbies or public spaces, and auto shows



Flexible Dimensions and Installation


Uslim is available in two sizes: 500x500mm or 500x1000mm, and can be hung, wall-mounted, fixed frame mounted, stacked, the possibilities are endless.







Installation and Maintenance





Uslim features a unique push and pull design between module and cabinet. When it comes to maintenance, complete front and rear service is available.

Modules are magnetically captive to the frame allowing for flexible mounting; hung, wall mounted, fixed frame mounted, or stacked.

Parameter	Value
Pixel Pitch	3.9mm
LED Type	3-in-1 SMD
Brightness	5,500 cd/m²
Pixels Per Panel	128 x 256 pixels
Pixel Density	65,536 pixels/m²
Weight	14.8 kg (32.6 lbs)
Module Size	W250mm x H250mm / 9.8in x 9.8in
Cabinet Size	W500mm x H500mm x D83.3mm / 19.7in x 19.7in x 3.3in
	W500mm x H1,000mm x D79mm / 19.7in x 39.2in x 3.1in
Aspect Ratio	1:1
Material	Die-casting Aluminum
Ingress Protection	IP65
Operating Temperature/Humidity	-20°~ +50° / 10~90%RH
Storage Temperature/Humidity	-30°~ +60° / 10~95%RH
Maintenance	Intelligent Front Service
Horizontal / Vertical Viewing Angle	+/-140° / +/-120°
Color Temperature	2000-9300K Adjustable
Brightness Control	Manual/Automatic
Contrast Ratio	3500:1
Input Power (Max/Typical)	350W/117W per panel
Video Frame Rate	50/60 Hz
Refresh Rate	1920 - 2880 Hz
Input Voltage	100~240VAC
Input Power Frequency	50~60 Hz
Input Signal	DVI/HDMI/VGA/SDI/DP/AV
Calibration	Support brightness and chroma
Mounting Configurations	Fixed, Floor-mounted, Hung