# Unilumin



## USI 4.8

#### • Flexible Application.

- Flexible Dimensions, Available in: 500x500mm OR 500x1000mm.
- Easy Maintenance.
- Multiple Installation Methods.

#### **Get Creative with Flexibility**

USlim can curve +- % degrees thanks to its built-in curve adjustment. This flexibility make display application almost endless: Uslim is an excellent option for retail spaces, corporate lobbies or public spaces, and auto shows



#### **Flexible Dimensions and Installation**

Uslim is available in two sizes: 500x500mm or 500x1000mm, and can be hung, wall-mounted, fixed frame mounted, stacked, the possibilities are endless.

Contact Us 844.263.3675 | www.unilumin-usa.com



### **Installation and Maintenance**



Uslim features a unique push and pull design between module and cabinet. When it comes to maintenance, complete front and rear service is available. Modules are magnetically captive to the frame allowing for flexible mounting; hung, wall mounted, fixed frame mounted, or stacked.

Parameter	Value
Pixel Pitch	4.8mm
LED Type	3-in-1 SMD
Brightness	1000 cd/m²
Pixels Per Panel	104 x 104 pixels
Pixel Density	65,536 pixels/m²
Weight	13 kg (28.7 lbs)
Module Size	W250mm x 250mm / 9.8in x 9.8in
Cabinet Size	W500mm x H500mm x D83.3mm / 19.7in x 19.7in x 3.3in
	W500mm x H1,000mm x D83.3mm / 19.7in x 39.2in x 3.3in
Aspect Ratio	1:1
Material	Die-casting Aluminum
Ingress Protection	IP30
Operating Temperature/Humidity	-10°~ +45° / 10~80%RH
Storage Temperature/Humidity	-20°~ +55° / 10~85%RH
Maintenance	Intelligent Front Service
Horizontal / Vertical Viewing Angle	140° / 120°
Color Temperature	2000-9300K Adjustable
Brightness Control	Manual/Automatic
Contrast Ratio	3000:1
Input Power (Max/Typical)	120W/40W per panel
Video Frame Rate	50/60 Hz
Refresh Rate	1920 - 2880 Hz
Input Voltage	100~240VAC
Input Power Frequency	50~60 Hz
Input Signal	DVI/HDMI/VGA/SDI/DP/AV
Calibration	Support brightness and chroma
Mounting Configurations	Fixed, Floor-mounted, Hung

Specifications are for reference only and are subject to change without notice.