



USportX10

OUTDOOR SOLUTION

- 4:3 Ratio, 16:9 Cabinet.
- Fast Installation & Disassembly.
- Protection & Backup.

4:3 Ratio, 16:9 Cabinet

4:3 module and 16:9 cabinet, can be spliced into 2K, 4K and 8K HD resolution.

Fast Installation & Disassembly

Convenient lock and magnetic module design.



Contact Us

844.263.3675 | www.unilumin-usa.com

Find Us @UniluminUSA





Redundancy Design
Power and signal backup available



Protection Design
Rubber cover on the top

Parameter	Value
Pixel Pitch	10mm
LED Type	3-in-1 Black SMD
Brightness	5,500 cd/m ² (nits) calibrated
Pixels Per Panel	160 x 90 pixels
Pixel Density	10,000 pixels/m ²
Weight Per Panel	60.5 kg (133.4 lbs)
Module Size	W400mm x H300mm x D24mm / (15.7in x 11.8in x 1in)
Cabinet Size	W1600mm x H900mm x D105mm / (63in x 35.4in x 4.1in)
Aspect Ratio	16:9
Material	Die-casting Aluminum
Ingress Protection	IP65
Operating Temperature/Humidity	-20°~ +50° / 10~90%RH
Storage Temperature/Humidity	-30°~ +60° / 10~95%RH
Maintenance	Rear
Horizontal / Vertical Viewing Angle	140° / 110°
Color Temperature	2000-9300K Adjustable
Brightness Control	Manual/Automatic
Contrast Ratio	5500:1
Input Power (Max/Typical)	1050W/315W per panel
Video Frame Rate	50/60 Hz
Refresh Rate	3840 Hz
Input Voltage	90~264V AC
Input Power Frequency	50~60 Hz
Input Signal	DVI/HDMI/VGA/SDI/DP/AV
Certification	TUV-CE/UL/CB/FC C/IC/RoHs

Specifications are for reference only and are subject to change without notice.