



## Unano 1.3

### INDOOR SOLUTION

- Smart Maintenance, Front Serviceability.
- High Grayscale and HDR Processing.
- 8:9 Unit Design.
- Edge Protection.

### Easy Maintenance

---

Intelligent front serviceability allows for fast, reliable maintenance.

Once a module is replaced, the calibration data will be upgraded automatically.



### Edge Protection

---

Edge protection at the bottom prevents damage with an automatic telescopic design, for safe and convenient re-disassembly.

# Hanging & Stacking Installation



Modules and precision aluminum cabinets are shipped separately for quick and easy installations.



With a simple hanging beam, 20 LED tiles can be hung in each column without an additional structure.

Parameter	Value
Pixel Pitch	1.3mm
LED Type	3-in-1 SMD
Brightness	600cd/m <sup>2</sup>
Pixels Per Panel	320 x 360 pixels
Pixel Density	522,257 pixels/m <sup>2</sup>
Weight	7 kg (15.4 lbs)
Module Size	W221.4mm x H166.05mm / 8.7in x 6.5in
Cabinet Size	W422.8mm x H498.15mm x D62mm / 16.65in x 19.6in x 2.4in
Aspect Ratio	8:9
Material	Die-casting Aluminum
Ingress Protection	IP50
Operating Temperature/Humidity	-10°~ +40° / 10~80%RH
Storage Temperature/Humidity	-20°~ 60° / 10~85%RH
Maintenance	Intelligent Front Service
Horizontal / Vertical Viewing Angle	160° / 160°
Color Temperature	2000-9500K Adjustable
Brightness Control	Manual/Automatic
Contrast Ratio	5000:1
Input Power (Max/Typical)	150W/50W per panel
Video Frame Rate	50/60 Hz
Refresh Rate	1920 Hz
Input Voltage	100~240VAC
Input Power Frequency	50~60 Hz
Input Signal	DVI/HDMI/VGA/SDI/DP/AV
Calibration	Support brightness and chroma
Mounting Configurations	Hung, Floor-mounted

Specifications are for reference only and are subject to change without notice.